



D-NS Series (Dual-MPPT, Single-Phase)

GoodWe D-NS series inverter adopts cutting-edge technology in photovoltaic fields, designed under modern industrial concept. Inheriting all the excellent traits from GoodWe SS and DS series, the D-NS series is much smarter in size and weight. Excellent cooling design, comprehensive software and hardware technology is guaranteed to maximize the life-span of these inverters.

- Up to 10 safety measurements
- DC switch
- IP65 dust-proof and water-proof
- 45°C full-load output
- Built-in anti-reverse function
- 30% lighter than similar products
- 20% Volume optimization
- Wide range of MPPT voltage
- Multiple monitoring and communication
- Fanless low-noise design

Technical Data	GW3000D-NS	GW3600D-NS	GW4200D-NS	GW5000D-NS
DC Input Data				
Max. allowed PV Power [W]	3900	4680	5460	6500
Nominal DC Power [W]	3300	3960	4600	5500
Max. DC voltage [V]	580	580	580	580
MPPT voltage range [V]	80~550	125~550	125~550	125~550
Starting voltage [V]	120	120	120	120
Max. DC current [A]	11/11	11/11	11/11	11/11
No. of DC connectors	2	2	2	2
No. of MPPTs	2 (can parallel)	2 (can parallel)	2 (can parallel)	2 (can parallel)
DC connector	MC4/ Phoenix/ Amphenol	MC4/ Phoenix/ Amphenol	MC4/ Phoenix/ Amphenol	MC4/ Phoenix/ Amphenol
AC Output Data				
Norminal AC power [W]	3000	3680	4200	5000*
Max. AC power [W]	3000	3680	4200	5000*
Max. AC current [A]	13.6	16	19	22.8
Norminal AC output	50/60Hz; 230Vac		50/60Hz; 230Vac	
AC output range	45~55Hz/55~65Hz; 180~270Vac		45~55Hz/55~65Hz; 180~270Vac	
THDi	<3%		<3%	
Power factor	0.8 leading~0.8 lagging		0.8 leading~0.8 lagging	
Grid connection	Single phase		Single phase	
Efficiency				
Max. efficiency	97.8%	97.8%	97.8%	97.8%
Euro efficiency	>97.5%	>97.5%	>97.5%	>97.5%
MPPT adaptation efficiency	99.9%	99.9%	99.9%	99.9%
Protection				
Residual current monitoring unit	Integrated	Integrated	Integrated	Integrated
Anti-islanding protection	Integrated	Integrated	Integrated	Integrated
DC switch	Integrated (optional)	Integrated (optional)	Integrated (optional)	Integrated (optional)
AC over current protection	Integrated	Integrated	Integrated	Integrated
Insulation monitoring	Integrated	Integrated	Integrated	Integrated
Certifications & Standards				
Grid regulation	VDE-AR-N 4105, EN50438, VDE0126-1-1, AS4777.2&.3, G83/G59	VDE-AR-N 4105, G83/G59, VDE0126-1-1, EN50438, AS4777.2&.3, MEA,PEA	VDE-AR-N 4105, EN50438, VDE0126-1-1, G83/G59	VDE-AR-N 4105, EN50438, VDE0126-1-1, G83/G59, AS4777.2&.3, MEA, PEA
Safety	IEC62109-1&-2, AS3100			
EMC	IEC/EN 61000-6-1, IEC/EN 61000-6-2, IEC/EN 61000-6-3, IEC/EN 61000-6-4, IEC/EN 61000-3-11, IEC/EN 61000-3-12			
General Data				
Dimensions (WxHxD) [mm]	347*432*145	347*432*145	347*432*145	347*432*145
Weight [kg]	14	14	14	14
Mounting	Wall bracket	Wall bracket	Wall bracket	Wall bracket
Ambient temperature range	-25~60°C (>45°C derating)	-25~60°C (>45°C derating)	-25~60°C (>45°C derating)	-25~60°C (>45°C derating)
Relative humidity	0~95%	0~95%	0~95%	0~95%
Max. operating altitude	4000m(> 3000m derating)	4000m(> 3000m derating)	4000m(> 3000m derating)	4000m(> 3000m derating)
Protection degree	IP65	IP65	IP65	IP65
Topology	Transformerless	Transformerless	Transformerless	Transformerless
Night power consumption [W]	<1	<1	<1	<1
Cooling	Natural convection	Natural convection	Natural convection	Natural convection
Noise emission [dB]	<25	<25	<25	<25
Display	LCD	LCD	LCD	LCD
Communication	USB2.0; RS485 or WiFi	USB2.0; RS485 or WiFi	USB2.0; RS485 or WiFi	USB2.0; RS485 or WiFi
Standard warranty [years]	5/10/15/20/25 (optional)	5/10/15/20/25 (optional)	5/10/15/20/25 (optional)	5/10/15/20/25 (optional)

*Note: 4600W for VDE-AR-N4105

Color Options